SECTION 2: Specifications

Specifications

SYSTEM/PROCESS	Roll-up envelope/card feeder designed to enhance the paper-feeding capabilities of the GR Series for increased productivity and versatility. Comes with required stand.
FEEDING SPEED	Equal to the speed of the Digital Duplicator (larger media may require slower Risograph operating speeds).
STOCK SIZE	Minimum: 3" X 5"; A6 (76.2mm X 127mm) Maximum: 11.7" X 13"; A3 (297mm X 143mm)
STOCK WEIGHT	Minimum: 20lb. Envelopes Maximum: 110lb. Index
REGISTRATION	+/- 1mm
FEED CAPACITY	Initial envelope capacity: 500 (#10 Business Envelopes) Continuous top-load, bottom-feed mechanism.
ACCESSORIES	Optional Conveyor at receiving end.
COMPATIBILITY	Compatible with GR Series and RISO Stand S-8925.
ELECTRICAL	110V/60Hz; 220V/50Hz
ENVIRONMENT	Temperature: 50 - 90 Fahrenheit Humidity: 30% - 90% Relative Humidity
SHIPPING WEIGHT	100lbs.
DIMENSIONS	28.5"W x 17.75"D x 30"H (excluding slide guides)

NOTE: The SF 3000 CANNOT be used with the Astro Envelope Feeder.

NOTE: The Risograph must be installed on Machine Stand S-8925

<<<Specifications are subject to change without notice.>>>